

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# b-chew bit 08223



## IT

### codice doganale

54075300.

### utilizzo

imbottiti, outdoor.

### caratteristiche

98% poliestere riciclato, 2% elastomero LYCRA®,  
altezza cm ± 140, peso 1050 gr/m².

### tintura

il prodotto è tinta in filo.

### lunghezza pezza

circa 20 mtl., disponibile anche al taglio con maggiorazione.

### abrasione

> 350.000 cicli, ISO 12947-2.

### solidità alla luce

6/7-7, ISO 105 B02.

### solidità allo sfregamento

secco 4/5, umido 4/5, ISO 105 X12.

### resistenza alla cucitura

orlito 2 mm, trama 2 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### sostenibilità

GRS®, OEKO-TEX®.

### resistenza al fuoco (work in progress)

1IM - UNI 9175; EN 1021 1/2;

BS 7176 + A1 medium hazard;

BS 5852 crib 5; NF-P 92 507 - M3;

NFPA 260 Class 1; California TB 117-2013;

IMO MED 3.20 - Ftp 307 part. 8; B-s1,d0 - EN 13501.

### attenzione

sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. consigliamo di verificare le schede tecniche di tutti i prodotti su [www.abitex.eu](http://www.abitex.eu)

## EN

### customs code

54075300.

### use

upholstered furniture, outdoor.

### features

98% recycled polyester, 2% LYCRA® elastomer,  
width cm ± 140, weight 1050 g/m².

### dyeing

yarn dyed product.

### roll length

approx. 20 lm, can also be cut-to-length at an extra cost.

### abrasion resistance

> 350.000 rubs, ISO 12947-2.

### colour fastness to light

6/7-7, ISO 105 B02.

### fastness to rubbing

dry 4/5, wet 4/5, ISO 105 X12.

### seam slippage

warp 2 mm, weft 2 mm, ISO 13936-2.

### pilling

4/5, ISO 12945-2.

### sustainability

GRS®, OEKO-TEX®.

### fire resistance (work in progress)

1IM - UNI 9175; EN 1021 1/2;

BS 7176 + A1 medium hazard;

BS 5852 crib 5; NF-P 92 507 - M3;

NFPA 260 Class 1; California TB 117-2013;

IMO MED 3.20 - Ftp 307 part. 8; B-s1,d0 - EN 13501.

### attention

slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. please check the technical data sheets of all products on the abitex website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



outdoor



sound  
absorbent



eco-friendly



recycled



year  
guarantee