

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# b-chew trio 08222



**IT**  
**codice doganale**  
54075300.

**utilizzo**  
imbottiti, outdoor.

**caratteristiche**  
98% poliestere riciclato, 2% elastomero LYCRA®,  
altezza cm ± 140, peso 850 gr/m².

**tintura**  
il prodotto è tinta in filo.

**lunghezza pezza**  
circa 20 mtl., disponibile anche al taglio con maggiorazione.

**abrasione**  
> 350.000 cicli, ISO 12947-2.

**solidità alla luce**  
6/7-7, ISO 105 B02.

**solidità allo sfregamento**  
secco 4/5, umido 4/5, ISO 105 X12.

**resistenza alla cucitura**  
ordito 2 mm, trama 2 mm, ISO 13936-2.

**pilling**  
4/5, ISO 12945-2.

**sostenibilità**  
GRS®, OEKO-TEX®.

**resistenza al fuoco (work in progress)**

1IM - UNI 9175; EN 1021 1/2;  
BS 7176 + A1 medium hazard;  
BS 5852 crib 5; NF-P 92 507 - M3;  
NFPA 260 Class 1; California TB 117-2013;  
IMO MED 3.20 - Ftp 307 part. 8; B-s1,d0 - EN 13501.

**attenzione**  
sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. consigliamo di verificare le schede tecniche di tutti i prodotti su [www.abitex.eu](http://www.abitex.eu)

**EN**  
**customs code**  
54075300.

**use**  
upholstered furniture, outdoor.

**features**  
98% recycled polyester, 2% LYCRA® elastomer,  
width cm ± 140, weight 850 g/m².

**dyeing**  
yarn dyed product.

**roll length**  
approx. 20 lm , can also be cut-to-length at an extra cost.

**abrasion resistance**  
> 350.000 rubs, ISO 12947-2.

**colour fastness to light**  
6/7-7, ISO 105 B02.

**fastness to rubbing**  
dry 4/5, wet 4/5, ISO 105 X12.

**seam slippage**  
warp 2 mm, weft 2 mm, ISO 13936-2.

**pilling**  
4/5, ISO 12945-2.

**sustainability**  
GRS®, OEKO-TEX®.

**fire resistance (work in progress)**

1IM - UNI 9175; EN 1021 1/2;  
BS 7176 + A1 medium hazard;  
BS 5852 crib 5; NF-P 92 507 - M3;  
NFPA 260 Class 1; California TB 117-2013;  
IMO MED 3.20 - Ftp 307 part. 8; B-s1,d0 - EN 13501.

**attention**  
slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. please check the technical data sheets of all products on the abitex website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



outdoor



sound  
absorbent



eco-friendly



recycled



year  
guarantee