

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

horo 33 / studio#21 st11 arabesque 04249 008



IT codice doganale

55121990.

utilizzo

tende, imbottiti, assorbimento acustico.

caratteristiche

100% poliestere, altezza cm \pm 140, peso \pm 560 gr/m².

tintura

il prodotto è tinto in pezza.

lunghezza pezze

circa 30 mtl., disponibile anche al taglio con maggiorazione.

abrasione

> 40.000 cicli, ISO 12947-2.

solidità alla luce

5, ISO 105 B02.

solidità allo sfregamento

secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura

orlito 3 mm, trama 3 mm, ISO 13936-2.

pilling

4/5, ISO 12945-2.

resistenza al fuoco

1IM - UNI 9175; Classe 1 - UNI 9177;

Class 1 - EN 13773; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

DIN 4102 - B1; NF-P 92 503 - M1;

NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;

California TB 117:2013; IMO MED - Ftp 307 part 8;

ONCOM B 3825 - normal brennbar.

attenzione

sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori.

consigliamo di verificare le schede tecniche di tutti i prodotti su www.abitex.eu

EN customs code

55121990.

use

curtains, upholstered furniture, sound absorption.

features

100% polyester, width cm \pm 140, weight \pm 560 g/m².

dyeing

piece dyed product.

roll length

approx. 30 lm, can also be cut-to-length at an extra cost.

abrasion resistance

> 40.000 rubs, ISO 12947-2.

colour fastness to light

5, ISO 105 B02.

fastness to rubbing

dry 4/5, wet 4, ISO 105 X12.

seam slippage

warp 3 mm, weft 3 mm, ISO 13936-2.

pilling

4/5, ISO 12945-2.

fire resistance

1IM - UNI 9175; Classe 1 - UNI 9177;

Class 1 - EN 13773; EN 1021 part 1/2;

BS 7176 + A1 medium hazard; BS 5852 crib 5;

DIN 4102 - B1; NF-P 92 503 - M1;

NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;

California TB 117:2013; IMO MED - Ftp 307 part 8;

ONCOM B 3825 - normal brennbar.

attention

slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. please check the technical data sheets of all products on the abitex website www.abitex.eu



fireproof



imo-med



sound
absorbent



customize
colors



printable



proposition
65



year
guarantee