

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

aida / studio#21 st08 vienna straw 04039 007



IT
codice doganale
58013700.

utilizzo
tende, imbottiti.

caratteristiche
100% poliestere, altezza cm $\pm$ 140, peso $\pm$ 435 gr/m².

tintura
il prodotto è tinto in pezza.

lunghezza pezza
circa 40 mtl., disponibile anche al taglio con maggiorazione.

abrasione
> 40.000 cicli, ISO 12947-2.

solidità alla luce
5, ISO 105 B02.

solidità allo sfregamento
secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura
ordito 3 mm, trama 2 mm, ISO 13936-2.

pilling
5, ISO 12945-2.

resistenza al fuoco
1IM - UNI 9175; Classe 1 - UNI 9177;
Class 1 - EN 13773; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NF-P 92 503 - M1; DIN 4102 - B1; NFPA 260;
NFPA 701 pass; California TB 117:2013;
IMO MED - Ftp 307 part 8; ÖNOM B 3825.

attenzione
sono ammesse leggere differenze di colore tra differenti partite. consigliamo di verificare le schede tecniche di tutti i prodotti su www.abitex.eu

EN
customs code
58013700.

use
curtains, upholstered furniture.

features
100% polyester, width cm $\pm$ 140, weight $\pm$ 435 g/m².

dyeing
piece dyed product.

roll length
approx. 40 lm., can also be cut-to-length at an extra cost.

abrasion resistance
> 40.000 rubs, ISO 12947-2.

colour fastness to light
5, ISO 105 B02.

fastness to rubbing
dry 4/5, wet 4, ISO 105 X12.

seam slippage
warp 3 mm, weft 2 mm, ISO 13936-2.

pilling
5, ISO 12945-2.

fire resistance
1IM - UNI 9175; Classe 1 - UNI 9177;
Class 1 - EN 13773; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NF-P 92 503 - M1; DIN 4102 - B1; NFPA 260;
NFPA 701 pass; California TB 117:2013;
IMO MED - Ftp 307 part 8; ÖNOM B 3825.

attention
slight colour differences between different batches are allowed. please check the technical data sheets of all products on the [abitex website www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



sound
absorbent



customize
colors



printable



proposition
65



year
guarantee