

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# horo 33 / studio#21 st03 jungle jum 04249 004



**IT**  
**codice doganale**  
55121990.

**utilizzo**  
tende, imbottiti, assorbimento acustico.

**caratteristiche**  
100% poliestere, altezza cm  $\pm$  140, peso  $\pm$  560 gr/m<sup>2</sup>.

**tintura**  
il prodotto è tinto in pezza.

**lunghezza pezze**  
circa 30 mtl., disponibile anche al taglio con maggiorazione.

**abrasione**  
> 40.000 cicli, ISO 12947-2.

**solidità alla luce**  
5, ISO 105 B02.

**solidità allo sfregamento**  
secco 4/5, umido 4, ISO 105 X12.

**resistenza alla cucitura**  
orlito 3 mm, trama 3 mm, ISO 13936-2.

**pilling**  
4/5, ISO 12945-2.

**resistenza al fuoco**  
1IM - UNI 9175; Classe 1 - UNI 9177;  
Class 1 - EN 13773; EN 1021 part 1/2;  
BS 7176 + A1 medium hazard; BS 5852 crib 5;  
DIN 4102 - B1; NF-P 92 503 - M1;  
NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;  
California TB 117:2013; IMO MED - Ftp 307 part 8;  
ONCOM B 3825 - normal brennbar.

**attenzione**  
sono ammesse leggere differenze di colore tra differenti partite, non ci assumiamo nessuna responsabilità per il trasferimento di colore/pigmenti causato da abbigliamento e accessori. consigliamo di verificare le schede tecniche di tutti i prodotti su [www.abitex.eu](http://www.abitex.eu)

**EN**  
**customs code**  
55121990.

**use**  
curtains, upholstered furniture, sound absorption.

**features**  
100% polyester, width cm  $\pm$  140, weight  $\pm$  560 g/m<sup>2</sup>.

**dyeing**  
piece dyed product.

**roll length**  
approx. 30 lm, can also be cut-to-length at an extra cost.

**abrasion resistance**  
> 40.000 rubs, ISO 12947-2.

**colour fastness to light**  
5, ISO 105 B02.

**fastness to rubbing**  
dry 4/5, wet 4, ISO 105 X12.

**seam slippage**  
warp 3 mm, weft 3 mm, ISO 13936-2.

**pilling**  
4/5, ISO 12945-2.

**fire resistance**  
1IM - UNI 9175; Classe 1 - UNI 9177;  
Class 1 - EN 13773; EN 1021 part 1/2;  
BS 7176 + A1 medium hazard; BS 5852 crib 5;  
DIN 4102 - B1; NF-P 92 503 - M1;  
NF-D 60 013 (AM 18); NFPA 260; NFPA 701 pass;  
California TB 117:2013; IMO MED - Ftp 307 part 8;  
ONCOM B 3825 - normal brennbar.

**attention**  
slight colour differences between different batches are allowed, we assume no responsibility for the transfer of colour/pigment caused by clothing and accessories. please check the technical data sheets of all products on the abitex website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



sound  
absorbent



customized  
colors



printable



proposition  
65



10  
year  
guarantee