

abitex

abitex srl
via del cristo 84
33044 manzano
ud - italy

t +39 0432 746060
www.abitex.eu
info@abitex.eu

FR300 (natural roots) petit melange 08227



IT
codice doganale
55121990.

utilizzo
imbottiti.

caratteristiche
100% poliestere, altezza cm $\pm$ 140, peso $\pm$ 355 gr/m².

tintura
il prodotto è tinta in filo.

lunghezza pezze
circa 35 mt., disponibile anche al taglio con maggiorazione.

abrasione
> 50.000 cicli, ISO 12947-2.

solidità alla luce
5, ISO 105 B02.

solidità allo sfregamento
secco 4/5, umido 4, ISO 105 X12.

resistenza alla cucitura
ordito 4 mm, trama 2 mm, ISO 13936-2.

pilling
4, ISO 12945-2.

sostenibilità
Oeko-tex®.

resistenza al fuoco
11M - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NFPA 260 - Class 1; California TB 117:2013;
IMO MED - Ftp 307 part 8.

resistenza al fuoco, solo su richiesta
Class 1 - UNI 9177; Class 1 - EN 13773; ÖNOM B 3825.

attenzione
sono ammesse leggere differenze di colore tra differenti partite. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su www.abitex.eu

EN
customs code
55121990.

use
upholstered furniture.

features
100% polyester, width cm $\pm$ 140, weight $\pm$ 355 g/m².

dyeing
yarn dyed product.

roll length
approx. 35 lm, can also be cut-to-length at an extra cost.

abrasion resistance
> 50.000 rubs, ISO 12947-2.

colour fastness to light
5, ISO 105 B02.

fastness to rubbing
dry 4/5, wet 4, ISO 105 X12.

seam slippage
warp 4 mm, weft 2 mm, ISO 13936-2.

pilling
4, ISO 12945-2.

sustainability
Oeko-tex®.

fire resistance
11M - UNI 9175; EN 1021 part 1/2;
BS 7176 + A1 medium hazard; BS 5852 crib 5;
NFPA 260 - Class 1; California TB 117:2013;
IMO MED - Ftp 307 part 8.

fire resistance, only on request
Class 1 - UNI 9177; Class 1 - EN 13773; ÖNOM B 3825.

attention
slight colour differences between different batches are allowed. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website www.abitex.eu



fireproof



imo-med



standard
100



year
guarantee