

# abitex

abitex srl  
via del cristo 84  
33044 manzano  
ud - italy

t +39 0432 746060  
www.abitex.eu  
info@abitex.eu

# FR450 (natural roots) chenille 04266



**IT**  
**codice doganale**  
54077200.

**utilizzo**  
imbottiti.

**caratteristiche**

100% poliestere, altezza cm  $\pm$  140, peso  $\pm$  490 gr/m<sup>2</sup>.

**tintura**

il prodotto è tinta in pezza.

**lunghezza pezze**

circa 40 mt., disponibile anche al taglio con maggiorazione.

**abrasione**

> 50.000 cicli, ISO 12947-2.

**solidità alla luce**

4/5, ISO 105 B02.

**solidità allo sfregamento**

secco 4/5, umido 4, ISO 105 X12.

**resistenza alla cucitura**

ordito 3 mm, trama 3 mm, ISO 13936-2.

**pilling**

4, ISO 12945-2.

**sostenibilità**

Oeko-tex®.

**resistenza al fuoco**

11M - UNI 9175; EN 1021 part 1/2;  
BS 7176 + A1 medium hazard; BS 5852 crib 5;  
NFPA 260 - Class 1; California TB 117:2013;  
IMO MED - Ftp 307 part 8.

**resistenza al fuoco, solo su richiesta**

Class 1 - UNI 9177; Class 1 - EN 13773; ÖNOM B 3825.

**attenzione**

sono ammesse leggere differenze di colore tra differenti partite. le schede tecniche vengono costantemente aggiornate sul sito, pertanto vi invitiamo a verificare online i dati del prodotto su [www.abitex.eu](http://www.abitex.eu)

**EN**  
**customs code**  
54077200.

**use**

upholstered furniture.

**features**

100% polyester, width cm  $\pm$  140, weight  $\pm$  490 g/m<sup>2</sup>.

**dyeing**

piece dyed product.

**roll length**

approx. 40 lm, can also be cut-to-length at an extra cost.

**abrasion resistance**

> 50.000 rubs, ISO 12947-2.

**colour fastness to light**

4/5, ISO 105 B02.

**fastness to rubbing**

dry 4/5, wet 4, ISO 105 X12.

**seam slippage**

warp 3 mm, weft 3 mm, ISO 13936-2.

**pilling**

4, ISO 12945-2.

**sustainability**

Oeko-tex®.

**fire resistance**

11M - UNI 9175; EN 1021 part 1/2;  
BS 7176 + A1 medium hazard; BS 5852 crib 5;  
NFPA 260 - Class 1; California TB 117:2013;  
IMO MED - Ftp 307 part 8.

**fire resistance, only on request**

Class 1 - UNI 9177; Class 1 - EN 13773; ÖNOM B 3825.

**attention**

slight colour differences between different batches are allowed. as technical data sheets are updated from time to time, we invite you to verify the latest document published for each item on the website [www.abitex.eu](http://www.abitex.eu)



fireproof



imo-med



standard  
100



year  
guarantee